


908 AUTHENTIC




Embossing:	EIR
V-groove:	yes, 4 sides
Base Material Composition:	100% Polyvinyl chloride
Project Suitable:	Yes
Total Height:	2.5 mm
Wear Layer Thickness:	0.55 mm
Number of M2 in Packaging:	3.48 M2
Number in Packaging:	30
Fire Class:	Bfl - S1
Suitable for Underfloor Heating:	Yes - up to 27 degrees max
Slip Sensitivity Topside:	Ja
Heat Permeability:	0.036 Kw/m2
Country of Origin:	China
Tariff Code:	39181090




AVAILABLE IN:



Description:	Authentic 8011 15,24x76,20 VPE: 3,484m2
PVC Pattern:	Herringbone
Color Spectrum:	Natural
PVC Color:	Natural oak



Description:	Authentic 8012 15,24x76,20 VPE: 3,484m2
PVC Pattern:	Herringbone
Color Spectrum:	Beige
PVC Color:	Light oak



Description:	Authentic 8013 15,24x76,20 VPE: 3,484m2
PVC Pattern:	Herringbone
Color Spectrum:	Beige
PVC Color:	Light oak

908

AUTHENTIC



Description: Authentic 8014 15,24x76,20 VPE: 3,484m2
PVC Pattern: Herringbone
Color Spectrum: Natural
PVC Color: Natural oak



Description: Authentic 8015 15,24x76,20 VPE: 3,484m2
PVC Pattern: Herringbone
Color Spectrum: Natural
PVC Color: Natural oak



Description: Authentic 8016 15,24x76,20 VPE: 3,484m2
PVC Pattern: Herringbone
Color Spectrum: Natural
PVC Color: Natural oak



Description: Authentic 8017 15,24x76,20 VPE: 3,484m2
PVC Pattern: Herringbone
Color Spectrum: Natural
PVC Color: Natural oak



Description: Authentic 8018 15,24x76,20 VPE: 3,484m2
PVC Pattern: Herringbone
Color Spectrum: Natural
PVC Color: Natural oak

Due to production techniques, colors may vary. Weight and size indications are always approximate.

[View Online](#)