



Embossing:	EIR
V-groove:	yes, 4 sides
Base Material Composition:	100% Polyvinyl chloride
Project Suitable:	Yes
Total Height:	2.5 mm
Wear Layer Thickness:	0.55 mm
Number of M2 in Packaging:	3.34 M2
Number in Packaging:	36
Fire Class:	Bfl - S1
Sound Damping:	4 Db
Suitable for Underfloor Heating:	Yes - up to 27 degrees max
Slip Sensitivity Topside:	Ja
Static Charging:	<2,0
Heat Permeability:	0.036 Kw/m2
Country of Origin:	China
Tariff Code:	39181090



AVAILABLE IN:

Description: PVC Pattern: Color Spectrum: PVC Color:	Pure 4011 15,24x60,96 VPE: 3,34m2 Herringbone Beige Light oak
Description: PVC Pattern: Color Spectrum: PVC Color:	Pure 4012 15,24x60,96 VPE: 3,34m2 Herringbone Brown Dark oak
Description: PVC Pattern: Color Spectrum: PVC Color:	Pure 4014 15,24x60,96 VPE: 3,34m2 Herringbone Beige Light oak

Page 1/2

Hamat B.V. Spoelstraat 16 8281 JT Genemuiden The Netherlands sales@hamat.com

14 April 2024

Hamat B.V. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system. The tests have been carried out according to the prescribed standards.



Due to production techniques, colors may vary. Weight and size indications are always approximate.



Page 2/2

Hamat B.V. Spoelstraat 16 8281 JT Genemuiden The Netherlands sales@hamat.com 14 April 2024

Hamat B.V. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system. The tests have been carried out according to the prescribed standards.